HomeMaker 390 Vinyl Sliding Glass Door

The 390 sliding glass door will brighten any room in your home with its large viewing areas and precise attention to detail. With **simple, clean lines, strong construction, and energy-efficient features**, you'll admire the craftsmanship and performance of your new door for years to come.

PERFORMANCE FEATURES

- Warm-edge spacer system maximizes energy efficiency and improves seal performance of insulated glass units
- Welded, multi-chambered vinyl frame for superior strength and energy efficiency
- Interlock at center rail provides a tight seal against air infiltration
- Double weatherstripping for protection against wind, rain, dust, and noise



Designed smarter, from the inside out

ENGINEERED TO PERFORM

- 4 ⁷/₈" frame depth
- 1" insulated glass
- 5 frame styles available

CONVENIENCE & STYLE

The 390 features the following design detail on every door:

Roll-form screen frame

SAFETY & SECURITY FEATURES

- Dual mortise lock provides secure closure
- Metal reinforcement at latch and meeting rail enhance strong construction
- Standard tempered glass is four times stronger than non-tempered glass and safer if broken
- Available with key-lock handle for added security and convenience

SIZING

MINIMUM & MAXIMUM (available in ¹/₈" increments)

- 2-Panel
 47"-119" wide × 71 ½"-96" high
- 3-Panel
 70"-144" wide × 71 1/2"-96" high
- 4-Panel
- 117 1/2"-144" wide x 71 1/2"-96" high

ENERGY-EFFICIENT GLASS PACKAGES

Our **dual-pane** insulated glass package options help save on heating and cooling costs while enhancing home comfort

- In cool weather, insulated glass provides outstanding thermal performance to keep interior glass surfaces closer to room temperature, eliminating cold spots near doors
- In warm weather, it helps reduce solar heat gain and minimize glare to improve interior comfort
- Able to meet ENERGY STAR® requirements in all four climate zones

GLAZING TYPE	U-VALUE	SHGC	STC
Lodz-366 glass, Intercept® spacer	0.33	0.23	28
Lo \tilde{E}^3 -366 glass, Intercept spacer, and grids	0.33	0.21	28
Argon, LoĒ ³ -366 glass, Intercept spacer	0.29	0.23	28
Argon, Lo \tilde{E}^3 -366 glass, Intercept spacer, and grids	0.29	0.20	28
LoĒ ³ -366 glass, Intercept Ultra spacer	0.32	0.23	28
LoĒ ³ -366 glass, Intercept Ultra spacer, and grids	0.32	0.21	28
Argon, LoĒ ³ -366 glass, Intercept Ultra spacer	0.28	0.23	28
Argon, Lo \bar{E}^3 -366 glass, Intercept Ultra spacer, and grids	0.28	0.20	28

Note: Values based on ¹⁵/₁₆" sculptured grids and tempered glass. Additional glass options are available.



OUR MISSION

Getting It Right Every Time

We build each of our products the same way we built our company: with integrity and precision. Every MI window and door is handcrafted in the United States using state-of-the-art manufacturing techniques, and is backed by vigorous in-house testing procedures. We are 100% committed to offering the styles, value, and performance you're after.

Discover everything we have to offer at miwindows.com, or by calling 1-717-365-3300.

Color-matched

GRID TYPES & SIZES

• 5/8" flat grids-between-the-glass

CREATE A CUSTOMIZED LOOK

- ¹⁵/₁₆" sculptured grids-between-the-glass
- 5/8" simulated divided light
- ¹⁵/₁₆" simulated divided light

GRID PATTERNS



PANEL OPERATION*







EXTERIOR LAMINATE



 View from outside looking in X=operating; O=stationary

Almond available on fin frame only. Not available with auto lock or SuperCapSR

Experience Clarity[™]